

SILENCE[®]

— VALDINOCI —

POWERED BY
KOHLER.

A RANGE OF SOUNDPROOFED POWER PACK ENGINES READY FOR INSTALLATION



KDW SERIES



KDI SERIES

SILENCE[®]

- ▼ Iron base.
- ▼ Noise-proof canopy in thermoformed ABS. Removable access doors for ordinary maintenance. Easily removable canopy for extraordinary maintenance.
- ▼ Control panel with tachometer and hour counter.
- ▼ Exhaust silencer.

KDW SERIES

- ▼ Power range from 18 to 37 kW.
- ▼ Stage III A emissions.

KDI SERIES

- ▼ Power range from 37 to 56 kW.
- ▼ Stage III B / Tier 4 Final emissions.



VALDINOCI LUIGI S.p.a.

Via Antico Acquedotto, 19 • 47122 Forlì • ITALIA • Tel. +39 0543 720 909 • www.valdinoci.it • info@valdinoci.it

STURDY AND RESISTANT SUITABLE FOR MANY APPLICATIONS

KDW SERIES

MODEL	ENGINE KOHLER	DISPLACEMENT cm ³	POWER (NB)* kW	NOISE** dB(A)	WEIGHT*** kg	DIMENSIONS (L x W x H) cm	EMISSIONS
SV1025	KDW 1003	1028	18,0 @ 3000	72	260	90 x 71 x 83,5	/
SV1430	KDW 1404	1372	22,5 @ 3000	72	273	90 x 71 x 83,5	Stage III A
SV1640	KDW 1603	1649	29,0 @ 3000	75	313	90 x 71 x 83,5	Stage III A
SV2250	KDW 2204	2199	36,6 @ 3000	75	341	90 x 71 x 83,5	Stage III A

KDI SERIES

MODEL	ENGINE KOHLER	DISPLACEMENT cm ³	POWER (NB)* kW	NOISE** dB(A)	WEIGHT*** kg	DIMENSIONS (L x W x H) cm	EMISSIONS
SV1955	KDI 1903 TCR	1861	42,0 @ 2600	73	487	120 x 90 x 94	Stage III B Tier 4 Final
SV2550	KDI 2504 M	2482	36,4 @ 2600	-	490	120 x 90 x 94	Stage III A
SV2575	KDI 2504 TCR	2482	55,4 @ 2600	74	525	120 x 90 x 94	Stage III B Tier 4 Final

* ISO 3046 IFN • ** taken at 7 meters @ (2800 rpm - KDW) (2200 rpm - KDI) • *** oil and cooling liquid included
These measured technical data (+/-1%) are preliminary information and may be subject to changes.

SILENCE KDW SERIES • (18-37 kW)

STANDARD EQUIPMENT

- Base incorporated 40 liters fuel tank
- SAE 4-7" 1/2 flanging (SV1640 and SV2250)
- SAE 5-6" 1/2 flanging (SV1025 and SV1430)
- Electric accelerator with step by step key
- Emergency stop button
- Control panel with tachometer and hour counter
- 12 V electric start
- Exhaust silencer
- Oil extraction pump

OPTIONAL ACCESSORIES

- Hydraulic pump adapters on 1st PTO (all models)
- Hydraulic pump adapters on 3rd PTO (SV1640 and SV2250)
- Cylindrical shaft extensions
- Industrial lever clutches
- 24 V electric start

SILENCE KDI SERIES • (37-56 kW)

STANDARD EQUIPMENT

- SAE 4-7" 1/2 flanging
- Electric accelerator with step by step key (SV2550 only)
- Electric accelerator with potentiometer knob
- Emergency stop button
- Control panel with tachometer, hour counter and engine check
- 12 V electric start
- Electric fuel pump
- Fuel cooler (SV2550 and SV2575)
- Exhaust silencer
- External OBD port

OPTIONAL ACCESSORIES

- Hydraulic pump adapters on 1st PTO and 3rd PTO
- Cylindrical shaft extensions
- Industrial lever clutches