

SV2250

DATA SHEET

POWER *:	36.6 kW @3000 rpm
MAX. TORQUE:	144.0 Nm @2000 rpm
NOISE LEVEL **:	75 dB(A)
WEIGHT *** :	341 Kg
DIMENSIONS (WxLxH):	71 x 90 x 83,5 cm
EMISSIONS COMPLIANCE:	2004/26 CE Stage III A
FUEL CONSUMPTION:	11,1 l/h

* POWER: ISO 3046 IFN

** NOISE: taken at 7 meters @2800 rpm without load

*** WEIGHT: oil and cooling liquid included

Measured technical data (+/- 1%) may be subject to changes.




STANDARD EQUIPMENT

Base incorporated 40 liters fuel tank
SAE 4 - 7" 1/2 flanging
Electric accelerator with step by step key
Control panel with tachometer and hour counter
12 V electric start
Exhaust silencer

OPTIONAL ACCESSORIES

Hydraulic pump adapter on 1st PTO
Hydraulic pump adapter on 3rd PTO
Cylindrical shaft extensions
Industrial hand lever clutches
24 V electric start

Engine: Kohler KDW 2204
Cylinders: 4
Displacement: 2199 cm³



SV2250

Bore (mm): 88
Stroke (mm): 90.4
Injection system: IDI
Compression ratio: 22.5:1
4-stroke diesel engine with in-line cylinders
Fluid-cooled with axial fan
Indirect injection
Geared distribution control
Forced lubrication with vane pump on the crankshaft
Cast iron cylinder head
Cast iron engine block with re-borable integral liners